

Fecha de Alta

17-01-2011

Versión

6 - 21/06/2023



**FAMILY**  
**LINE**

**PRODUCTOS PARA USO ESPECIFICO**  
**QUITAPINTURAS**

### DESCRIPTION AND NATURE

Semi-gel fast-acting stripper. For stripping all types of paint from any surface. Biodegradable, non-toxic. Methylene chloride free.

### USAGES

Outdoors/Indoors

Metal

Wood,

### PROPERTIES

- Optimal applicability
- Open time

It removes easily the paintings , by contact and some scrapping

do not enerates dust

Eliminates paints and varnishes

Does not harms wood

Does not alter its colour

Without acids

Without alcalis

Without cloruro metileno

### TECHNICAL CHARACTERISTCS

Referencia Color	QUITAMONT GEL
Finish	Transparent
Specific weight	0,96± 0,05 kg/l
Viscosity	44 +/- 5 PO
Solids in volume	3± 1
Solids in weight	3± 1
Aproximated performance by coat	3-6 m <sup>2</sup> /L

Dry to touch	Working Time: 10-20 min.
--------------	--------------------------

Dry to repaint	(20°C HR: 60%): 6 h
----------------	---------------------

Colours	Translucent, milky white
---------	--------------------------

### SURFACE PREPAIRING

#### New surfaces

Not applicable

#### Restoring and maintenance

See the following Application section.

### WAY OF USE

#### Application notes

1. Homogenise the product slowly using a spatula.

2. Apply with brush or spatula, depending on the thickness of coat to be stripped, leave to act for between 10 and 20 minutes.

Fecha de Alta

17-01-2011

Versión

6 - 21/06/2023

3. Remove softened paint with scraper or brush.
4. We strongly recommend testing the product on a small area before use to ensure suitability. If you have any questions, please consult the Technical Department.
5. Prior to repainting we recommend cleaning thoroughly with clean water and allowing to dry.

### Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	Uso
Roller	Uso
Pallete / spatula	Uso

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>Montoxyl range</b>			
<b>MAX</b>	No suele ser necesario		Sistema Gama madera familia 5
<b>STD</b>	No suele ser necesario		Sistema Gama madera familia 5
<b>Polyurethane lacquers and varnishes</b>			
<b>MAX</b>	Quitamont gel	Quitamont gel	Sistema Gama Madera familia 5
<b>STD</b>	Quitamont gel		Sistema Gama Madera familia 5
<b>Nitrocellulose lacquers and varnishes</b>			
<b>MAX</b>	Quitamont gel	Quitamont gel	Sistema Gama Madera familia 5
<b>STD</b>	Quitamont gel		Sistema Gama Madera familia 5
<b>Enamels and synthetic varnishes</b>			
<b>MAX</b>	Quitamont gel	Quitamont gel	Sistema Gama Madera Familia 5
<b>STD</b>	Quitamont gel		Quitamont gel
<b>Paints and watter lasures</b>			
<b>MAX</b>	Quitamont gel	Quitamont gel	Sistema Gama Madera Familia 5
<b>STD</b>	Quitamont gel		Quitamont gel

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

503512

# QUITAMONT GEL



Fecha de Alta

17-01-2011

Versión

6 - 21/06/2023

## PACKINGS

0.375 L, 0.75 L, 4 L