

NEVADA CONSTRUCTOR BLANCO



FAMILY
LINE

PAREDES Y TECHOS

MATE

DESCRIPTION AND NATURE

High-opacity, high-whiteness paint for walls and ceilings; ideal for large-scale projects and general interior use. Highly breathable.

USAGES

Indoors
Cement
Concrete
Brick
Plaster
Drywall (gypsum plasterboard): fibreboard

PROPERTIES

Gloss level: matt (according to UNE-EN 13300, at 85° reflectance < 10)

Washability: Class 3 (according to Standard UNE-EN 13300)

High sweating

Opacity: Class 2 for a performance of 8 m²/litre (according to Standard UNE-EN 13300)

TECHNICAL CHARACTERISTICS

Referencia Color	NEVADA CONSTRUCTOR BLANCO
Finish	Matt
Specific weight	1,59 ± 0,05 kg/l
Viscosity	90 +/- 10 PO
Solids in volume	45 ± 1
Solids in weight	66 ± 1
VOC	Cat. a/BA 75/30 (2007/2010): 1,42 g/l
Aproximated performance by coat	10-12 m ² /L

Dry to touch	(20°C HR: 60%): 1h
Dry to repaint	(20° C HR: 60%): 3-4h
Colours	White

SURFACE PREPAIRING

New surfaces

Cement and concrete mortars:

1. Wait till complete drying of product (30 days minimum).
2. Remove off any efflorescences by abrasive jet.
3. Neutralize alkaline surfaces.
4. Extremely polished surfaces should be sanpapered to open pores.
5. Remove off any foreing products or remains.
6. Bad condition surfaces should be anchored properly with Emulsión Fijadora or Fijamont..
7. Fill in defects in the substrate (see family 6).

Plaster, plaster-covered brick:

1. Wait till complete drying of product (20% max. Moisture level).
2. Remove off any foreign product or product remains.
3. Clean any efflorescence with a jet washer.
4. Use a sealant or matt paste to regulate surface absorption.
5. Extremely polished surfaces should be sandpapered to open pore.

6. Very damaged surfaces should be fixed with suitable product (Emulsión Fijadora or Fijamont).

Plasterboard partition walls:

1. Carry out a general sanding of the joints and putty fixing areas.
2. Then, clean them to ensure the substrate is free of dust, grease and other contaminants.
3. For application on coloured boards that tend to generate stains, apply Montoplac Sellador Antimanchas.

Restoring and maintenance

1. Remove off old paint completely.
2. Brilliant surfaces should be matted to ensure good adherence.
3. Check paint type and anchoring on painted surfaces to avoid incompatibilities. Remove off any dust or dirt before painting.
4. Cover surface imperfections with suitable putty or plaster (Plasmont).
5. Mildewed surfaces should be treated with Monto Limpia Moho.

WAY OF USE

Application notes

- Shake product until perfectly homogenized.
- First coat should be diluted depending on surface condition and porosity level.
- Finish with one or more coats slightly diluted until surface is totally covered.
- Do not apply product at temperatures below 5°C or any surfaces which have been exposed to sunshine.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	5 - 10%
Roller	5 - 10%
Air-less gun	10 - 30%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Project			
MAX	Fijamont o Emulsión Fijadora	Nevada Constructor	Nevada Constructor
STD	Nevada Constructor diluido		Nevada Constructor
Old paintings			
MAX	Fijamont o Emulsión Fijadora	Nevada Constructor	Nevada Constructor
STD	Nevada Constructor diluido		Nevada Constructor
Drywall (gypsum plasterboard)			
MAX	Fijamont o Emulsión Fijadora	Nevada Constructor	Nevada Constructor
STD	Nevada Constructor diluido		Nevada Constructor

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in fire. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in fire. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

15 L



FAMILY LINE

DESCRIPTION AND NATURE

High-opacity, high-whiteness paint for walls and ceilings; ideal for large-scale projects and general interior use. Highly breathable.

USAGES

PROPERTIES

Gloss level: matt (according to UNE-EN 13300, at 85° reflectance < 10)

Washability: Class 3 (according to Standard UNE-EN 13300)

High sweating

Opacity: Class 2 for a performance of 8 m²/litre (according to Standard UNE-EN 13300)

TECHNICAL CHARACTERISTICS

Referencia Color

Finish Matt

Specific weight 1,59± 0,05 kg/l

Viscosity 90 +/- 10 PO

Solids in volume 45± 1

Solids in weight 66± 1

VOC Cat. a/BA 75/30 (2007/2010):1,42 g/l

Aproximated performance by coat 10-12 m²/L

Dry to touch (20°C HR: 60%):1h

Dry to repaint (20° C HR: 60%):3-4h

Colours White

SURFACE PREPAIRING

New surfaces

Cement and concrete mortars:

1. Wait till complete drying of product (30 days minimum).
2. Remove off any efflorescences by abrasive jet.
3. Neutralize alkaline surfaces.

NEVADA CONSTRUCTOR BLANCO

4. Extremely polished surfaces should be sanpapered to open pores.
5. Remove off any foreing products or remains.
6. Bad condition surfaces should be anchored properly with Emulsión Fijadora or Fijamont..
7. Fill in defects in the substrate (see family 6).

Plaster, plaster-covered brick:

1. Wait till complete drying of product (20% max. Moisture level).
2. Remove off any foreign product or product remains.
3. Clean any efflorescence with a jet washer.
4. Use a sealant or matt paste to regulate surface absorption.
5. Extremely polished surfaces should be sandpapered to open pore.
6. Very damaged surfaces should be fixed with suitable product (Emulsión Fijadora or Fijamont).

Plasterboard partition walls:

1. Carry out a general sanding of the joints and putty fixing areas.
2. Then, clean them to ensure the substrate is free of dust, grease and other contaminants.
3. For application on coloured boards that tend to generate stains, apply Montoplac Sellador Antimanchas.

Restoring and maintenance

1. Remove off old paint completely,
2. Brilliant surfaces should be matted to ensure good adherence.
3. Check paint type and anchoring on painted surfaces to avoid incompatibilities. Remove off any dust or dirt before painting.
4. Cover surface imperfections with suitable putty or plaster (Plasmont).
5. Mildewed surfaces should be treated with Monto Limpia Moho.

WAY OF USE

Application notes

- Shake product until perfectly homogenized.
- First coat should be dilluted depending on surface conditon and porosity level.
- Finish with one or more coats slightly dilluted until surface is totally covered.
- Do not apply product at temperatures below 5°C or any surfaces which have been exposed to sunshine.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	5 - 10%
Roller	5 - 10%
Air-less gun	10 - 30%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Project			
MAX	Fijamont o Emulsión Fijadora	Nevada Constructor	Nevada Constructor
STD	Nevada Constructor diluido		Nevada Constructor
Old paintings			
MAX	Fijamont o Emulsión Fijadora	Nevada Constructor	Nevada Constructor
STD	Nevada Constructor diluido		Nevada Constructor
Drywall (gypsum plasterboard)			
MAX	Fijamont o Emulsión Fijadora	Nevada Constructor	Nevada Constructor
STD	Nevada Constructor diluido		Nevada Constructor

502771


Fecha de Alta

26-03-2026

Versión

1 - 16/09/2026

NEVADA CONSTRUCTOR BLANCO



SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

15 L