

Fecha de Alta

02-07-2026

Versión

1 - 21/08/2026



FAMILY
LINE

REVESTIMIENTOS DE FACHADAS
SILICATO

DESCRIPTION AND NATURE

Primer for preparing substrates prior to the application of Ovaldine Sol Silicato. Can also be used for thinning.

USAGES

- Outdoor / Indoor
- Mineral media
- Previously painted mineral substrates
- Prior to the application of Sol Silicato mineral paints

PROPERTIES

It fix the slippery mineral surfaces
It keeps the perspiration of the supports

TECHNICAL CHARACTERISTICS

Referencia Color	PRIMER SOL SILICATO
Finish	Colorless
Specific weight	1,01± 0,05 kg/l
Solids in volume	7± 1
Solids in weight	11± 1
VOC	Cat. c/BA 75/40 (2007/2010):0,97 g/l
Aproximated performance by coat	Depending of product usage
Dry to touch	2h
Dry to repaint	24h

SURFACE PREPAIRING

New surfaces

Cement mortar:

1. Wait until fully set (30 days minimum).
2. Remove any efflorescence from the substrate using abrasive blasting.
3. On excessively smooth surfaces, key lightly with sandpaper.
4. Stabilise friable substrates using PRIMER SOL SILICATO.
5. Remove any foreign materials and/or residues from the substrate.
6. Fill any defects in the substrate with a cement-based exterior-grade filler (see product range 6 - SUBSTRATE PREPARATION, the sections covering powder fillers, to make an appropriate selection).

Restoring and maintenance

1. On walls affected by mould, treat them first with Monto Limpia Moho.
2. Can be applied directly to mineral surfaces with old paintwork in good condition and firmly adhered. If there is any poorly adhered paint, remove all loose material before application.
3. Glossy surfaces should be lightly abraded to ensure good adhesion.
4. Fill defects in the substrate with a cement-based exterior-grade filler (see product range 6 - SUBSTRATE PREPARATION, the sections covering powder fillers to make the appropriate selection).

Fecha de Alta

02-07-2026

Versión

1 - 21/08/2026

WAY OF USE**Application notes****Solvent for dilution and cleaning**

Way of use	Aproximate dilution
Brush, roller or spray gun	0

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Mineral support			
MAX	Primer Sol Silicato	Ovaldine Sol Silicato	Ovaldine Sol Silicato
STD			
Pre-painted mineral substrate			
MAX	Primer sol silicato	Ovaldine Sol Silicato	Ovaldine Sol Silicato
STD			

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

4 L