

Fecha de Alta

21-04-2021

Versión

4 - 26/01/2026


FAMILY ALTA DECORACION / SISTEMAS TINTOMÉTRICOS

LINE SISTEMA MICROCEMENTO

DESCRIPTION AND NATURE

It is a water-based acrylic emulsion. It is part of the ODeco MicroCement System product suite. It acts as a binder for cementitious products. It is also the medium where the color is added.

USAGES

- Base tinting system for Microcement ODeco
- To mix with Microcement Base, Walls or Floors.

PROPERTIES

Strongness
Easy application
Water-based
Good colour production performance

TECHNICAL CHARACTERISTICS

Referencia Color	MICROCEMENT RESIN TR
Mixture relation	Según Parte A, ver modo de empleo
Specific weight	1,01± 0,05 kg/l
Solids in volume	24± 1
Solids in weight	27± 1
VOC	Cat. i/BA 140/140 (2007/2010): 1,18 g/l
Aproximated performance by coat	Depending of product usage
Colours	Colorless. Microcement ODeco color chart available with MONTOMIX.

SURFACE PREPAIRING
New surfaces

See the Microcement ODeco Technical Data Sheets, Base, Walls ó Floors.

Restoring and maintenance

See the Microcement ODeco Technical Data Sheets, Base, Walls ó Floors.

WAY OF USE
Application notes

In the accompanying bucket, pour the content of the resin.
On this, sprinkle, under gentle mechanical stirring, the powder from the bag.
Shake well for at least 5 min.

Mix ratio according to the product used:

- Microcement Base: 15kg of Part A: 5L of Part B (Microcement Resin)
- Microcement Floors: 13kg of Part A: 5L of Part B (Microcement Resin)
- Microcement Walls: 12kg of Part A: 5L of Part B (Microcement Resin)

Avoid leaving product of the mixture on the walls of the bucket, collecting regularly to prevent it from drying out.

Available special stainless trowel for white and pastel colors.

Fecha de Alta

21-04-2021

Versión

4 - 26/01/2026

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Methal pallette

Aproximate dilution

Según producto

Según producto

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Complete system overview			
MAX	MICROCEMENT PRIMER ABS ó N-ABS	MICROCEMENT BASE + MICROCEMENT FLOORS/WALLS	SEALER + MICROCEMENT PROTECTOR (2K)
STD	MICROCEMENT BASE	MICROCEMENT FLOORS/WALLS	SEALER + MICROCEMENT PROTECTOR DECO (1K)
Ground			
MAX	MICROCEMENT PRIMER ABS ó N-ABS	MICROCEMENT BASE + MICROCEMENT FLOORS	SEALER + MICROCEMENT PROTECTOR (2K)
STD	MICROCEMENT BASE	MICROCEMENT FLOORS	SEALER + MICROCEMENT PROTECTOR (2K)
Walls			
MAX	MICROCEMENT PRIMER ABS ó N-ABS	MICROCEMENT BASE + MICROCEMENT FLOOR/WALLS	SEALER+ MICROCEMENT PROTECTOR (2K)
STD	MICROCEMENT BASE	MICROCEMENT FLOORS/WALLS	SEALER+ MICROCEMENT PROTECTOR DECO (1K)

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 12 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adecuate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

5 Kg