

Fecha de Alta

09-07-2007

Versión

7 - 23/01/2026


FAMILY ALTA DECORACION / SISTEMAS TINTOMÉTRICOS

LINE METALIZADOS

DESCRIPTION AND NATURE

Finish product with a thin texture, an original and decorative metallic nacar or golden reflexes, giving luxurious and elegance sensation.

USAGES

Concrete
Gypsum Board

PROPERTIES

Adherence
Does not turn yellow
Elasticity
Working smoothness
Different decorative effects depending on application method
Easily repairable
Non absorbent
Micronized

TECHNICAL CHARACTERISTICS

Referencia Color	VELATO TERCIOPELO PLATA
Finish	Metallic reflexes
Specific weight	1,19± 0,05 kg/l
Viscosity	175 +/- 25 PO
Solids in volume	29± 1
Solids in weight	43± 1
VOC	Cat. I/BA 300/200 (2007/2010): 200,00 g/l
Aproximated performance by coat	7-10 m ² /L
Dry to touch	(20°C HR: 60%): 2-3h
Dry to repaint	(20°C HR: 60%): 6h
Colours	Base: 720 Gold Base, 900 Silver Base High Decoration card n° 9, attainable ones with Montomix system with base 720 or 900. Universal Montotinte or to maximum water 5%.

SURFACE PREPARING
New surfaces

Mortar of cement and plaster:

1. Hope until forged total (30 days minimum).
2. Clean the possible effloresces with abrasive spurt.
3. Neutralize the alkaline surfaces.
4. In excessively polished surfaces, you must sandpaper to open the pore.
5. Clean rest of products on support and/or remainders.
6. Fix the weak supports with suitable locking device (FIJADORA emulsion or FIJAMONT).
7. Fill the defects of the support (to see in family Putties the lines corresponding to make a suitable election).

Fecha de Alta

09-07-2007

Versión

7 - 23/01/2026

Plaster:

1. Wait for until well dry (max, 20% humidity).
2. Clean rest of products and/or remainders.
3. Eliminate the possible effloresces with abrasive spurt.
4. Regulate the absorptions of the surface by means of primer or one coat of same product very diluted.
5. In surfaces excessively polished to sandpaper to open the pore.
6. Fix the weak supports by means of EMULSION FIJADORA or FIJAMONT.
7. Fill with putty to eliminate the defects of the support.

Restoring and maintenance

1. Eliminate totally old paintings in badly state or badly adhered .
2. Clarify shining paintings to assure a good adhesion.
3. On painted supports you must verify the solidity and anchorage of the painting, to diagnose his nature to avoid possible incompatibilidades and to eliminate the dust and the dirt before painting.
4. Repare with plaste the defects of the support (to see in family 6 the lines corresponding to plastes).
5. Deal with Monto Limpia Moho the supports with mould.

WAY OF USE**Application notes**

Don't apply to inferior temperatures to 5°C nor with the support excessively warms up.

1. Once the support in good conditions:
2. Apply FONDO TERCIOPELO or a water paint like OVALDINE MATE.
it is not totally needed apply the FONDO TERCIOPELO or OVALDINE MATE with the same color as the VELATO TERCIOPELO
3. Apply VELATO TERCIOPELO with a spatula or trowel.

Draped finish.

or:

1. Apply FONDO VELATO TERCIOPELO or a water paint like OVALDINE MATE
1. Apply VELATO TERCIOPELO colored with the choosen color. with a spatula or trowel
2. Apply FONDO TERCIOPELO colored with a similar color as the VELATO TERCIOPELO with a Sponge or Tampons. .

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Sponge	Uso
Pallete / spatula	Uso
Cloth special roller	Uso
Tampons	Uso
Painting brush	Uso
Glove	Uso

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Support with mould			
MAX	Monto Limpia Moho + Fijador	Fondo Velato Terciopelo	Velato Terciopelo
STD	Monto Limpia Moho	Fondo Velato Terciopelo	Velato Terciopelo
Old paintings in bad state			
MAX	Emulsión Fijadora, Fijamont	Fondo Velato terciopelo	Velato terciopelo
STD	Emulsión Fijadora, Fijamont	Fondo Velato terciopelo	Velato terciopelo
Asphalt fabric			
MAX		Fondo Velato Terciopelo	Velato Terciopelo

Fecha de Alta

09-07-2007

Versión

7 - 23/01/2026

STD	Fondo Velato Terciopelo	Velato Terciopelo
------------	-------------------------	-------------------

Wood

MAX	Selladora Sellalux	Fondo Velato Terciopelo	Velato Terciopelo
------------	--------------------	-------------------------	-------------------

STD	Selladora Sellalux	Fondo Velato Terciopelo	Velato Terciopelo
------------	--------------------	-------------------------	-------------------

Cement

MAX	Emulsión Fijadora, Fijamont	Fondo Velato Terciopelo	Velato Terciopelo
------------	-----------------------------	-------------------------	-------------------

STD	Fondo Velato Terciopelo	Velato Terciopelo
------------	-------------------------	-------------------

Support weak

MAX	Emulsión Fijadora, Fijamont	Fondo Velato terciopelo	Velato terciopelo
------------	-----------------------------	-------------------------	-------------------

STD	Emulsión Fijadora, Fijamont	Fondo Velato terciopelo	Velato terciopelo
------------	-----------------------------	-------------------------	-------------------

Dry plasters and by-products

MAX	Emulsión Fijadora, Fijamont	Fondo Velato Terciopelo	Velato Terciopelo
------------	-----------------------------	-------------------------	-------------------

STD	Fondo Velato Terciopelo	Velato Terciopelo
------------	-------------------------	-------------------

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.62 L, 2.1 L