501304

Fecha de Alta
30-10-2008
Versión
8 - 05/11/2025

ACEITE DE TECA

FAMILY	**MADERA**
LINE	**ACEITES**

DESCRIPTION AND NATURE

Mixture of natural oils for the nutrition and protection of unvarnished wood. Reinforced with UV filter.

USAGES

Outdoors/Indoors
Wood

PROPERTIES

Optimal applicability
- Waterproof
Penetrating depth
- Doesn't film build
- Nourishes and beautifies the wood
- Easy maintenance
Reinforced with U.V. filter

TECHNICAL CHARACTERISTCS

Referencia Color	ACEITE DE TECA
Finish	Transparent
Specific weight	(0,83 ± 0,03)g/ml
Solids in volume	(49 ± 1)
Solids in weight	(53 ± 1)
Aproximated performance by coat	10-20 m²/L
Dry to touch	(20ºC HR:60%):24-48h
Dry to repaint	(20ºC HR:60%):>30min
Colours	Montomix Base: Pine, Teak, Walnut

SURFACE PREPAIRING

New surfaces
New woods:

- The support must be free of foreign products and/or residues.
- Apply to wood with a moisture content of less than 20%.
- Apply to healthy, well-degreased, dust-free and dry wood.
- For wood with resin stains on the inside (usually coniferous) and/or greasy tropical wood, it will be necessary to clean it first with a solvent.
- If the wood shows signs of aging, it must be previously sanded, eliminating the entire gray surface and removing dust by brushing or any other mechanical means.
- Spread the oil with the help of a trowel or roller, wait 15-30 min. In those areas with greater absorption, redistribute from the areas with excess product. Repeat the process until the piece is saturated with oil.
- Remove the surplus.

Restoring and maintenance
Oiled woods:

- The loss of shine over time indicates the deterioration of the oil.
- Repeat the process to renew the appearance and protection at this point.

- If they have been varnished with closed-pore varnishes such as Synthetic or Similar Varnishes, remove by stripping with Quitamont Universal or by mechanical means and proceed as with new wood.

WAY OF USE

Application notes

1.- General:

- Stir the product until it is perfectly homogenized.
- Apply to clean and dry substrates.
- Sand previously to ensure good penetration and leveling on the wood.
- Apply following the dilutions recommended in the Application Systems section.
- Do not apply the product at high temperatures, or on surfaces exposed to strong sunlight.
- Maintain good ventilation conditions during drying time.
- Do not apply with relative humidity greater than 80%
- Woods with resins and/or exotic fats, clean them first with solvent.
- Remove any excess that remains on the surface.

Solvent for dilution and cleaning

Solvent 1401

Way of use	Aproximate dilution
Painting brush	0%
Roller	0%
Cloth	0%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Wood			
MAX	Aceite de Teca	Aceite de Teca	Aceite de Teca
STD	Aceite de Teca		Aceite de Teca

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5º and 35ºC

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances.As it is impossible to stablish an adecuate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L, 5 L