

CATALIZADOR ACRIPOL PISCINAS



FAMILY PRODUCTOS PARA USO ESPECIFICO
LINE PISCINAS

DESCRIPTION AND NATURE

Product exclusive catalyst Acripol piscinas poliester.

USAGES

PROPERTIES

TECHNICAL CHARACTERISTICS

Referencia Color	CATALIZADOR ACRIPOL PISCINAS
Finish	.
Specific weight	0,97± 0,05 kg/l
Viscosity	14 +/- 2 SG
Solids in volume	40± 1
Solids in weight	47± 1
Aproximated performance by coat	Depending of product usage

SURFACE PREPAIRING

New surfaces

Restoring and maintenance

WAY OF USE

Application notes

- Respect the mixing ratio with part A.

Solvent for dilution and cleaning

Way of use Aproximate dilution

SYSTEM

Procedures depending of surface type

Primer

Intermedium

Finish

CATALIZADOR ACRIPOL PISCINAS

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 12 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.8 L