

502079

Fecha de Alta

23-11-2009

Versión

6 - 10/12/2025

# CATALIZADOR BARNIZ ACRIPOL

**MONTÓ**  
profesional


FAMILY

ESMALTES

LINE

POLIURETANOS MULTISOORTE

## DESCRIPTION AND NATURE

Catalyst exclusive Acripol Barniz and Anti-Pintadas

## USAGES

Outdoor/Indoor

## PROPERTIES

Strongness

## TECHNICAL CHARACTERISTICS

Referencia Color CATALIZADOR BARNIZ ACRIPOL

Mixture relation 4 (Barniz) : 1 (catalizador)

Specific weight  $1 \pm 0,05$  kg/l

Viscosity 18 +/- 3 SG

Solids in volume  $57 \pm 1$ Solids in weight  $61 \pm 1$ 

Aproximated performance by coat Depending of product usage

Colours Colorless

## SURFACE PREPAIRING

New surfaces

Restoring and maintenance

## WAY OF USE

### Application notes

-Mix with its corresponding varnish respecting the mixing proportions.

### Solvent for dilution and cleaning

Way of use                      Approximate dilution

## SYSTEM

Procedures depending of surface type

Primer

Intermedium

Finish

# CATALIZADOR BARNIZ ACRIPOL

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

Maximum recommended storage time : 12 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

0.15 L, 0.8 L