

Fecha de Alta

04-04-2014

Versión

7 - 20/01/2026


FAMILY PAVIMENTOS / SISTEMAS TINTOMÉTRICOS

LINE SEÑALIZACIÓN VIAL (AGUA)

DESCRIPTION AND NATURE

Water-soluble paint for floors with modified acrylic emulsion base. Quick-drying, with excellent adhesion and hardness on cement-type surfaces. Ideal for painting floors indoors and outdoors, for road markings, on asphalt media in good condition, terraces, driveways, etc.

USAGES

Outdoor/Indoor
Cement
Moulded concrete
Concrete
Cement mortars

PROPERTIES

Adherence
Strongness
Surface protection
Odourless when dry
Resistance to friction and hits
Anti-dust
Do not cause suppuration in asphaltic surfaces
Resistant to washing
Easily applicable
Water-based
Drying fast
U.V. resistant
Easy to repaint

TECHNICAL CHARACTERISTICS

Referencia Color	PAVIMONT ACQUA BLANCO
Finish	Semi-matt
Specific weight	1,26± 0,05 kg/l
Viscosity	100 +/- 10 KU
Solids in volume	41± 1
Solids in weight	55± 1
VOC	Cat. i/BA 140/140 (2007/2010): 20,15 g/l
Aproximated performance by coat	6-9 m ² /L
Dry to touch	10-30min
Dry to repaint	1-2h
Colours	White 102, Grey 189, Red 152, Blue Zone 184, Green 128, Daffodil Yellow 130. Colors of the RAL letter group A, B and C.
	TR base

SURFACE PREPARING
New surfaces

Masonry surfaces (cement and derivatives):

1. Treat these surfaces in the usual way, removing saltpetre, excess moisture and efflorescence.

Fecha de Alta

04-04-2014

Versión

7 - 20/01/2026

2. Treat the surface to achieve the desired porosity.
3. Remove foreign products and/or residues.

Restoring and maintenance

- Clean, mend and fill any parts in poor condition.
- Remove flaking or poorly adhered paint.
- If necessary, sand for better adhesion and to get the right degree of porosity.

WAY OF USE**Application notes**

- A spot test before application is always advisable.
- Stir the product until perfectly blended.
- Do not apply the product at high temperatures or on surfaces exposed to strong insolation.
- Humidity of flooring: maximum of 4% measured at a depth of 2 cm.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Air-less gun	0 - 10 %
Aerographic gun	10 - 25 %
Brush, Roller	0 - 15 %

SYSTEM**Procedures depending of surface type**

	Primer	Intermedium	Finish
Cement			
MAX	PAVIMONT ACQUA	PAVIMONT ACQUA	BARNIZ PAVIMONT ACQUA
STD	PAVIMONT ACQUA		PAVIMONT ACQUA

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L, 4 L, 15 L