

Fecha de Alta

07-05-2009

Versión

4 - 09/01/2026


FAMILY PREPARACIONES, FONDOS E IMPR.

LINE MASILLAS EN POLVO

DESCRIPTION AND NATURE

Powdered filler for smoothing textured surfaces, can be applied in thick coats. Very easy to sand.

USAGES

 Indoors
 Concrete
 Plaster
 Plaster

PROPERTIES

 Optimal applicability
 No flammable
 Fast drying
 High thickness coats
 It fix very good over Matt Water Paintings
 Minimum decrease
 Adhesion even for "wet on wet"
 Long open time
 Maximum recommended thickness : 7mm
 Very easy to sand

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT LIJAFACIL
Finish	Matt
Specific weight	2,49± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%):5-6h
Dry to repaint	(20°C HR: 60%):24-48h
Colours	White

SURFACE PREPAIRING
New surfaces

Plaster and cement mortar:

- Test suitability on surface.
- Wait till complete drying of product (30 days).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply as recommended under Application Systems and Application points.
- For extremely damaged surfaces, use suitable fixer before putting.

Restoring and maintenance

- Remove off any remains or chipping of product or any other foreign product. Open pore by sandpapering or any other mechanical systems. Test adherence level and treat as per new surfaces.

Fecha de Alta

07-05-2009

Versión

4 - 09/01/2026

WAY OF USE

Application notes

- Use clean and rust-free tools detailed in the Application System.
- Anchor adequately.
- We usually recommend coats of between 5-7 mm at most.
- Three or more coats can be applied to a thickness of up to 15 mm.
- Repaint following the indicated period of time. Given that this depends on the levels of humidity, temperature and thickness of the coat, the lack of clogging of the sandpaper with indicate that the product is ready for repainting.
- Suitable finishing products: Ovaldine, Montoplástica, Montonature, Esmalte Montosintético, Luxatín and High Decoration products.
- Prior to applying the finish, it is recommended to vacuum up any dust produced during sanding and apply a fixative.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallette / spatula

Aproximate dilution

400ml de agua por kg

400ml de agua por kg

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New work			
MAX	Emulsión fijadora, Fijamont	Plasmont lijafacil	Montoplástica, Montonature, Ovaldine, Montosintetic, Luxatín, Alta decoración.
STD	Plasmont lijafacil	Emulsión fijadora, Fijamont	Montoplástica, Montonature, Ovaldine, Montosintetic, Luxatín, Alta decoración.
Plasterboard			
MAX	Plasmont lijafacil	Plasmont lijafacil	Montoplástica, Montonature, Ovaldine, Montosintético, Luxatín, Alta decoración.
STD	Plasmont lijafacil	Fijador (Emulsón fijadora, Fijamont	Montoplástica, Montonature, Ovaldine, Montosintético, Luxatín, Alta decoración.

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances.As it is impossible to stablish an adequate description for every nature and status of the supports to be

Fecha de Alta

07-05-2009

Versión

4 - 09/01/2026

Painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

5 Kg, 15 Kg



FAMILY LINE

DESCRIPTION AND NATURE

Powdered filler for smoothing textured surfaces, can be applied in thick coats. Very easy to sand.

USAGES

PROPERTIES

Optimal applicability
 No flammable
 Fast drying
 High thickness coats
 It fix very good over Matt Water Paintings
 Minimum decrease
 Adhesion even for "wet on wet"
 Long open time
 Maximum recommended thickness : 7mm
 Very easy to sand

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	2,49± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1

Aproximated performance by coat Depending of product usage

Dry to touch	(20°C HR: 60%):5-6h
Dry to repaint	(20°C HR: 60%):24-48h
Colours	White

SURFACE PREPAIRING

New surfaces

Plaster and cement mortar:


- Test suitability on surface.
- Wait till complete drying of product (30 days).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply as recommended under Application Systems and Application points.
- For extremely damaged surfaces, use suitable fixer before puttying.

Fecha de Alta

07-05-2009

Versión

4 - 09/01/2026



Restoring and maintenance

- Remove off any remains or chipping of product or any other foreign product. Open pore by sandpàpering or any other mechanical systems. Test adherence level and treat as per new surfaces.

WAY OF USE

Application notes

- Use clean and rust-free tools detailed in the Application System.
- Anchor adequately.
- We usually recommend coats of between 5-7 mm at most.
- Three or more coats can be applied to a thickness of up to 15 mm.
- Repaint following the indicated period of time. Given that this depends on the levels of humidity, temperature and thickness of the coat, the lack of clogging of the sandpaper with indicate that the product is ready for repainting.
- Suitable finishing products: Ovaldine, Montoplástica, Montonature, Esmalte Montosintético, Luxatín and High Decoration products.
- Prior to applying the finish, it is recommended to vacuum up any dust produced during sanding and apply a fixative.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallete / spatula

Aproximate dilution

400ml de agua por kg

400ml de agua por kg

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New work			
MAX	Emulsión fijadora, Fijamont	Plasmont Ilijafacil	Montoplástica, Montonature, Ovaldine, Montosintetic, Luxatín, Alta decoraci3n.
STD	Plasmont Ilijafacil	Emulsión fijadora, Fijamont	Montoplástica, Montonature, Ovaldine, Montosintetic, Luxatín, Alta decoraci3n.
Plasterboard			
MAX	Plasmont Ilijafacil	Plasmont Ilijafacil	Montoplástica, Montoneture, Ovaldine, Montosintético, Luxatín, Alta decoraci3n.
STD	Plasmont Ilijafacil	Fijador (Emuls3n fijadora, Fijamont	Montoplástica, Montoneture, Ovaldine, Montosintético, Luxatín, Alta decoraci3n.

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

502303


PLASMONT LIJAFACIL

Fecha de Alta

07-05-2009

Versión

4 - 09/01/2026



NOTE

PACKINGS

5 Kg, 15 Kg