

Fecha de Alta

04-07-2007

Versión

7 - 09/01/2026



FAMILY
LINE

PREPARACIONES, FONDOS E IMPR.

MASILLAS AL USO

DESCRIPTION AND NATURE

Ready-to-use, superelastic, waterproofing mastic with fibers for the targeted treatment of cracks and fissures.

USAGES

Outdoors/Indoors

Cement, Plaster, Concrete, Brick

Common construction surfaces: plaster, cement, plasterboard, fiber cement, plasterboard, old paintings in good condition, etc.

Partitioning: fiberboard, laminated plaster, plasterboard or similar

Repair of cracks, sealing of joints, filling of holes

PROPERTIES

Elasticity

Water-resistant

Minimum decrease

No cracking at all

Odourless when dry

Good applicability

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT FIBRA ELASTICO
Finish	Matt
Specific weight	1,36± 0,05 kg/l
Solids in volume	53± 1
Solids in weight	68± 1
Minimum recommended thickness	1 mm
Aproximated performance by coat	Depending of product usage

Dry to touch	(20°C HR: 60%, 1mm): 4-8h
Dry to repaint	24-48h
Colours	White

SURFACE PREPAIRING

New surfaces

- Use the tools indicated in the application system, clean and rust-free.
- Apply to clean, dry substrates.
- Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.
- Maintain good ventilation during the drying time.
- Do not apply at relative humidity levels above 80%.
- Recoat with a second coat to avoid possible shrinkage.
- Repaint after the product has completely dried.

Restoring and maintenance

- Abrir posibles grietas o fisuras hasta fondo saneado, eliminar el polvo producido mediante cepillo o brocha.
- Eliminar del soporte productos extraños mal adheridos o en mal estado, abrir el poro caso de estar cerrado mediante lijado u otro medio mecánico.
- Proceder como en soportes nuevos.

Fecha de Alta

04-07-2007

Versión

7 - 09/01/2026

WAY OF USE

Application notes

- Use the tools indicated in the application system, clean and rust-free.
- Apply to clean, dry substrates.
- Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.
- Maintain good ventilation during the drying time.
- Do not apply at relative humidity levels above 80%.
- Recoat with a second coat to avoid possible shrinkage.
- Repaint after the product has completely dried.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallette / spatula

Aproximate dilution

al uso

al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Wood			
MAX	Fijamont / Emulsión Fijadora	Plasmont Fibra Elástico	Familia 4
STD		Plasmont Fibra Elástico	Familia 4
Interior new/old buildings			
MAX	Fijador (Emulsión Fijadora)	Plasmont Fibra Elastico	Fijador (Emulsión Fijadora) / Familia 1
STD		Plasmont Fibra Elastico	Fijador (Emulsión Fijadora) / Familia 1
Outer old work painted badly state			
MAX	Fijador (Emulsión Fijadora)	Plasmont Fibra Elástico	Fijador (Emulsión Fijadora) / Familia 2 ó Familia 3
STD	Plasmont Fibra Elástico	Fijador (Emulsión Fijadora)	Familia 2 ó Familia 3

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 36 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

Fecha de Alta

04-07-2007

Versión

7 - 09/01/2026

PACKINGS

0.75 L, 2.5 L



FAMILY LINE

DESCRIPTION AND NATURE

Ready-to-use, superelastic, waterproofing mastic with fibers for the targeted treatment of cracks and fissures.

USAGES

PROPERTIES

Elasticity
Water-resistant
Minimum decrease
No cracking at all
Odourless when dry
Good applicability

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	1,36± 0,05 kg/l
Solids in volume	53± 1
Solids in weight	68± 1
Minimum recommended thickness	1 mm
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%, 1mm): 4-8h
Dry to repaint	24-48h
Colours	White

SURFACE PREPAIRING

New surfaces

- Use the tools indicated in the application system, clean and rust-free.
- Apply to clean, dry substrates.
- Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.
- Maintain good ventilation during the drying time.
- Do not apply at relative humidity levels above 80%.
- Recoat with a second coat to avoid possible shrinkage.
- Repaint after the product has completely dried.

Restoring and maintenance


- Abrir posibles grietas o fisuras hasta fondo saneado, eliminar el polvo producido mediante cepillo o brocha.
- Eliminar del soporte productos extraños mal adheridos o en mal estado, abrir el poro caso de estar cerrado mediante lijado u otro medio mecánico.
- Proceder como en soportes nuevos.

Fecha de Alta

04-07-2007

Versión

7 - 09/01/2026



WAY OF USE

Application notes

- Use the tools indicated in the application system, clean and rust-free.
- Apply to clean, dry substrates.
- Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.
- Maintain good ventilation during the drying time.
- Do not apply at relative humidity levels above 80%.
- Recoat with a second coat to avoid possible shrinkage.
- Repaint after the product has completely dried.

Solvent for dilution and cleaning

Water

Way of use

Stainless trowel

Pallette / spatula

Aproximate dilution

al uso

al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Wood			
MAX	Fijamont / Emulsión Fijadora	Plasmont Fibra Elástico	Familia 4
STD		Plasmont Fibra Elástico	Familia 4
Interior new/old buildings			
MAX	Fijador (Emulsión Fijadora)	Plasmont Fibra Elastico	Fijador (Emulsión Fijadora) / Familia 1
STD		Plasmont Fibra Elastico	Fijador (Emulsión Fijadora) / Familia 1
Outer old work painted badly state			
MAX	Fijador (Emulsión Fijadora)	Plasmont Fibra Elástico	Fijador (Emulsión Fijadora) / Familia 2 ó Familia 3
STD	Plasmont Fibra Elástico	Fijador (Emulsión Fijadora)	Familia 2 ó Familia 3

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

502305


PLASMONT FIBRA ELASTICO

Fecha de Alta

04-07-2007

Versión

7 - 09/01/2026



PACKINGS

0.75 L, 2.5 L