

Fecha de Alta

25-06-2007

Versión

4 - 04/02/2026


**FAMILY** PREPARACIONES, FONDOS E IMPR.

**LINE** MASILLAS EN POLVO

**DESCRIPTION AND NATURE**

Powdered filler for smoothing textured surfaces, can be applied in thick layers. Specially suitable for smoothing textured surfaces.

**USAGES**

Indoors

Walls made of brick or other materials that tend to leave marks or stains when painted

Concrete

Plaster

**PROPERTIES**

Adherence

Optimal applicability

No flammable

Fast drying

High thickness coats

It fix very good over Matt Water Paintings

Easy sandable

Minimum decrease

Long open time

Maximum recommended thickness : 7mm

**TECHNICAL CHARACTERISTICS**

Referencia Color	PLASMONT RENOVACION
Finish	Matt
Specific weight	2,5± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%): 4-5h
Dry to repaint	(20°C HR: 60%): 24-48h
Colours	White

**SURFACE PREPAIRING**
**New surfaces**

Plaster and cement mortar:

- Test PLASMONT RENOVACION suitability on surface.
- Wait till complete drying of product (30 days).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT RENOVACION as recommended under Application Systems and Application points.
- For extremely damaged surfaces, use suitable fixer (see family 6) before puttying.
- Recommended maximum thickness per coat should always be observed.

Fecha de Alta

25-06-2007

Versión

4 - 04/02/2026

**Restoring and maintenance**

- Remove off any remains or chipping of product or any other foreign product. Open pore by sandpàpering or any other mechanical systems.
- Test adherence level and treat as per new surfaces.

**WAY OF USE****Application notes**

- Use clean and rust-free tools detailed in the Application System.
- Anchor adequately.
- We usually recommend coats of between 5-7 mm at most.
- Three or more coats can be applied to a thickness of up to 15 mm.
- Repaint following the indicated period of time. Given that this depends on the levels of humidity, temperature and thickness of the coat, the lack of clogging of the sandpaper with indicate that the product is ready for repainting.
- Suitable finishing products: Ovaldine, Montoplástica, Montonature, Esmalte Montosintético, Luxatín and High Decoration products.

**Solvent for dilution and cleaning**

Water

**Way of use**

Stainless trowel

Pallette / spatula

**Aproximate dilution**

400ml de agua por kg

400ml de agua por kg

**SYSTEM****Procedures depending of surface type**

	Primer	Intermedium	Finish
<b>New work</b>			
<b>MAX</b>	Emulsión fijadora, Fijamont, Fijalite	Plasmont renovación	Montoplástica, Montonature, Ovaldine, Montosintetic, Luxatín, Alta decoración.
<b>STD</b>	Plasmont renovación	Emulsión fijadora, Fijamont	Montoplástica, Montonature, Ovaldine, Montosintetic, Luxatín, Alta decoración.
<b>Plasterboard</b>			
<b>MAX</b>	Plasmont renovación	Plasmont renovación	Montoplástica, Montonature, Ovaldine, Montosintético, Luxatín, Alta decoració.
<b>STD</b>	Plasmont renovación	Fijador (Emulsón fijadora, Fijamont	Montoplástica, Montonature, Ovaldine, Montosintético, Luxatín, Alta decoració.

**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Fecha de Alta

25-06-2007

Versión

4 - 04/02/2026

## NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

5 Kg, 15 Kg



## FAMILY LINE

### DESCRIPTION AND NATURE

Powdered filler for smoothing textured surfaces, can be applied in thick layers. Specially suitable for smoothing textured surfaces.

## USAGES

## PROPERTIES

Adherence  
Optimal applicability  
No flammable  
Fast drying  
High thickness coats  
It fix very good over Matt Water Paintings  
Easy sandable  
Minimum decrease  
Long open time  
Maximum recommended thickness : 7mm

## TECHNICAL CHARACTERISTICS

Referencia Color	
Finish	Matt
Specific weight	2,5± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%): 4-5h
Dry to repaint	(20°C HR: 60%): 24-48h
Colours	White

## SURFACE PREPAIRING

Fecha de Alta

25-06-2007

Versión

4 - 04/02/2026

**New surfaces**

Plaster and cement mortar:

- Test PLASMONT RENOVACION suitability on surface.
- Wait till complete drying of product (30 days).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreing products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT RENOVACION as recommended under Application Systems and Application points.
- For extremely damaged surfaces, use suitable fixer (see family 6) before puttying.
- Recommended maximum thickness per coat should always be observed.

**Restoring and maintenance**

- Remove off any remains or chipping of product or any other foreign product. Open pore by sandpàpering or any other mechanical systems.
- Test adherence level and treat as per new surfaces.

**WAY OF USE****Application notes**

- Use clean and rust-free tools detailed in the Application System.
- Anchor adequately.
- We usually recommend coats of between 5-7 mm at most.
- Three or more coats can be applied to a thickness of up to 15 mm.
- Repaint following the indicated period of time. Given that this depends on the levels of humidity, temperature and thickness of the coat, the lack of clogging of the sandpaper with indicate that the product is ready for repainting.
- Suitable finishing products: Ovaldine, Montoplástica, Montonature, Esmalte Montosintético, Luxatín and High Decoration products.

**Solvent for dilution and cleaning**

Water

**Way of use**

Stainless trowel

Pallette / spatula

**Aproximate dilution**

400ml de agua por kg

400ml de agua por kg

**SYSTEM****Procedures depending of surface type**

	Primer	Intermedium	Finish
<b>New work</b>			
<b>MAX</b>	Emulsión fijadora, Fijamont, Fijalite	Plasmont renovación	Montoplástica, Montonature, Ovaldine, Montosintetic, Luxatín, Alta decoración.
<b>STD</b>	Plasmont renovación	Emulsión fijadora, Fijamont	Montoplástica, Montonature, Ovaldine, Montosintetic, Luxatín, Alta decoración.
<b>Plasterboard</b>			
<b>MAX</b>	Plasmont renovación	Plasmont renovación	Montoplástica, Montonature, Ovaldine, Montosintético, Luxatín, Alta decoració.
<b>STD</b>	Plasmont renovación	Fijador (Emulsón fijadora, Fijamont	Montoplástica, Montonature, Ovaldine, Montosintético, Luxatín, Alta decoració.


**SECURITY**

Fecha de Alta

25-06-2007

Versión

4 - 04/02/2026



Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE****PACKINGS**

5 Kg, 15 Kg