

Fecha de Alta

04-07-2007

Versión

3 - 12/01/2026


**FAMILY** PREPARACIONES, FONDOS E IMPR.

**LINE** MASILLAS MADERA

**DESCRIPTION AND NATURE**

Standard putty in a range of colours for restoring, repairing and moulding wood before painting.

**USAGES**

Indoors

Wood after varnished

Restoring furniture, frames, crack filler, defects

**PROPERTIES**

Does not decrease  
Covers imperfections  
Base putty  
Fast sanding  
Good adhesion  
No cracking at all

**TECHNICAL CHARACTERISTICS**

Referencia Color	PLASMONT MADERA NATURAL
Finish	Matt
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%, 1mm): 5-10min
Dry to repaint	(20°C HR: 60%, 1mm): 1-2h
Colours	Natural, Pino, Haya, Roble, Nogal, Teka, Sapeli, Caoba

**SURFACE PREPAIRING**
**New surfaces**

Wood:

- Remove external products and/or residues from the wood.
- Apply to clean and dry wood.
- Back gouge cracks or fissures back to repaired base and remove the dust.
- Apply as instructed in the Application Systems and Application.

**Restoring and maintenance**

Varnished and lacquered wood:

- Remove old paint with paint stripper or other means until healthy wood is uncovered.
- Proceed as you would for a new surface

**WAY OF USE**
**Application notes**

- Apply several coats, at least two, using a spatula.
- Allow to dry between coats.
- Apply the final coat generously and leave to dry for 1 to 2 hours before sanding.
- Allow to dry completely before varnishing or painting.
- Paint or varnish with Selladora Sellalux, synthetic enamels and synthetic varnishes, Montolac products or Montopol products, following the instructions provided in their technical specifications.

Fecha de Alta

04-07-2007

Versión

3 - 12/01/2026

## Solvent for dilution and cleaning

Solvent 1407

**Way of use**                      **Aproximate dilution**  
 Palleta / spatula                      0

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>Old/New interior Wood</b>			
<b>MAX</b>	Plasmont madera	Plasmont madera	Esmaltes barnices y madera Monto
<b>STD</b>	Plasmont madera	Plasmont madera	Esmaltes barnices y madera Monto

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

0.12 Kg



**FAMILY  
LINE**

## DESCRIPTION AND NATURE

Standard putty in a range of colours for restoring, repairing and moulding wood before painting.

## USAGES

## PROPERTIES


Does not decrease  
Covers imperfections

Fecha de Alta

04-07-2007

Versión

3 - 12/01/2026



Base putty  
Fast sanding  
Good adhesion  
No cracking at all

## TECHNICAL CHARACTERISTICS

Referencia Color

Finish Matt

Approximated performance by coat Depending of product usage

Dry to touch (20°C HR: 60%, 1mm): 5-10min

Dry to repaint (20°C HR: 60%, 1mm): 1-2h

Colours Natural, Pino, Haya, Roble, Nogal, Teka, Sapeli, Caoba

## SURFACE PREPAIRING

### New surfaces

Wood:

- Remove external products and/or residues from the wood.
- Apply to clean and dry wood.
- Back gouge cracks or fissures back to repaired base and remove the dust.
- Apply as instructed in the Application Systems and Application.

### Restoring and maintenance

Varnished and lacquered wood:

- Remove old paint with paint stripper or other means until healthy wood is uncovered.
- Proceed as you would for a new surface

## WAY OF USE

### Application notes

- Apply several coats, at least two, using a spatula.
- Allow to dry between coats.
- Apply the final coat generously and leave to dry for 1 to 2 hours before sanding.
- Allow to dry completely before varnishing or painting.
- Paint or varnish with Selladora Sellalux, synthetic enamels and synthetic varnishes, Montolac products or Montopol products, following the instructions provided in their technical specifications.

### Solvent for dilution and cleaning

Solvent 1407

### Way of use

Pallette / spatula

### Aproximate dilution

0

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>Old/New interior Wood</b>			
<b>MAX</b>	Plasmont madera	Plasmont madera	Esmaltes barnices y madera Monto
<b>STD</b>	Plasmont madera	Plasmont madera	Esmaltes barnices y madera Monto


## SECURITY

Fecha de Alta

04-07-2007

Versión

3 - 12/01/2026



Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE****PACKINGS**

0.12 Kg