

Fecha de Alta

06-03-2008

Versión

6 - 09/01/2026

**FAMILY** PREPARACIONES, FONDOS E IMPR.**LINE** MASILLAS HIERRO Y METALES**DESCRIPTION AND NATURE**

Two-component bodybuilder type polyester paste putty with excellent anchorage on iron and metals and other materials. With high filling power designed to cover defects and level surfaces before painting.

**USAGES**

Outdoors/Indoors

Iron

Galvanized iron

Polyester

Cement mortars

**PROPERTIES**

Elasticity

Levelling

Thixotropic

Fast drying

Base putty

Fast sanding

High filling power, given its high solids content.

Good adhesion

Easy to sand

Drying fast

No cracking at all

**TECHNICAL CHARACTERISTICS**

Referencia Color	PLASMONT METALES CREMA
Mixture relation	100 partes (masilla): 2-2.5 (Catalizador Masilla)
Finish	Matt
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%): 5-10min
Dry to repaint	(20°C HR: 60%): 30min
Colours	Putty

**SURFACE PREPAIRING****New surfaces**

- To clean all the strange product support and/or remainders.
- To apply on clean, dry, sandpaperings and taken the grease out of bottoms.
- To open to possible outcries or fissures until adjusted bottom and to eliminate remainders and produced dust.
- To apply so and as indicates in the sections Application.

**Restoring and maintenance**

- To eliminate old paintings by means of pickling or any other procedure, until healthy bottom.
- To come as in new supports.

Fecha de Alta

06-03-2008

Versión

6 - 09/01/2026

## WAY OF USE

### Application notes

To mix both components in the suitable proportion. To mix only the amount to use during the time of life of the mixture. To apply the product with a spatula. You let dry. To sandpaper in dry with grain sandpaper P-80 or P-240. Once sandpapering to come the painted one with the chosen painting.  
Tª <5°C polyester putties harden not

### Solvent for dilution and cleaning

Solvent 1406

### Way of use

Pallette / spatula

### Aproximate dilution

0

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>Old/New interior Wood</b>			
<b>MAX</b>	Plasmont Metales	Imprimación Pintura de Acabado	Acropol, Montoepox
<b>STD</b>	Plasmont Metales	Imprimación Pintura de Acabado	Montosintético, Luxatín
<b>Metal decoration</b>			
<b>MAX</b>	Plasmont metales	Imprimación Pintura Acabado	Acropol, Montoepox
<b>STD</b>	Plasmont metales	Imprimación Pintura Acabado	Montosintético, Luxatín
<b>Plastic</b>			
<b>MAX</b>	Plasmont metales	Imprimación Pintura de Acabado	Acropol, Montoepox
<b>STD</b>	Plasmont metales	Imprimación Pintura de Acabado	Montosintético, Luxatín

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

Maximum recommended storage time : 12 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

1 Kg

Fecha de Alta

06-03-2008

Versión

6 - 09/01/2026



## FAMILY LINE

### DESCRIPTION AND NATURE

Two-component bodybuilder type polyester paste putty with excellent anchorage on iron and metals and other materials. With high filling power designed to cover defects and level surfaces before painting.

### USAGES

### PROPERTIES

Elasticity  
 Levelling  
 Thixotropic  
 Fast drying  
 Base putty  
 Fast sanding  
 High filling power, given its high solids content.  
 Good adhesion  
 Easy to sand  
 Drying fast  
 No cracking at all

### TECHNICAL CHARACTERISTICS

Referencia Color	
Mixture relation	100 partes (masilla): 2-2.5 (Catalizador Masilla)
Finish	Matt
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%): 5-10min
Dry to repaint	(20°C HR: 60%): 30min
Colours	Putty

### SURFACE PREPAIRING

#### New surfaces

- To clean all the strange product support and/or remainders.
- To apply on clean, dry, sandpaperings and taken the grease out of bottoms.
- To open to possible outcries or fissures until adjusted bottom and to eliminate remainders and produced dust.
- To apply so and as indicates in the sections Application.

#### Restoring and maintenance

- To eliminate old paintings by means of pickling or any other procedure, until healthy bottom.
- To come as in new supports.

### WAY OF USE

#### Application notes

To mix both components in the suitable proportion. To mix only the amount to use during the time of life of the mixture. To apply the product with a spatula. You let dry. To sandpaper in dry with grain sandpaper P-80 or P-240. Once sandpapering to come the painted one with the chosen painting.

Fecha de Alta

06-03-2008

Versión

6 - 09/01/2026

Tª &lt;5°C polyester putties harden not

**Solvent for dilution and cleaning**

Solvent 1406

**Way of use**

Pallette / spatula

**Aproximate dilution**

0

**SYSTEM****Procedures depending of surface type**

	Primer	Intermedium	Finish
<b>Old/New interior Wood</b>			
<b>MAX</b>	Plasmont Metales	Imprimación Pintura de Acabado	Acripol, Montoepox
<b>STD</b>	Plasmont Metales	Imprimación Pintura de Acabado	Montosintético, Luxatín
<b>Metal decoration</b>			
<b>MAX</b>	Plasmont metales	Imprimación Pintura Acabado	Acripol, Montoepox
<b>STD</b>	Plasmont metales	Imprimación Pintura Acabado	Montosintético, Luxatín
<b>Plastic</b>			
<b>MAX</b>	Plasmont metales	Imprimación Pintura de Acabado	Acripol, Montoepox
<b>STD</b>	Plasmont metales	Imprimación Pintura de Acabado	Montosintético, Luxatín

**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE****PACKINGS**

1 Kg