

Fecha de Alta

29-07-2011

Versión

2C - 04/12/2025



FAMILY PAREDES Y TECHOS / SISTEMAS TINTOMÉTRICOS
LINE MATE

DESCRIPTION AND NATURE

Plastic paint with ecological certificate High performance, coverage and levelling. This product contributes to LEED®, BREEAM® and VERDE certifications.

USAGES

Indoors
 Walls and ceilings
 Cement mortars
 Concrete
 Brick
 Plaster
 Dripping effect
 Drywall (gypsum plasterboard): fibreboard

PROPERTIES



Gloss level: matt (according to UNE-EN 13300, at 85° reflectance < 10)

With European Ecological Certificate

Complies with the ecological criteria set out in the Commission's Decision of 13/08/2008 on the award of the Community Ecolabel to indoor paints and varnishes.

Washability: Class 2 (according to Standard UNE-EN 13300)

Gardner Washability Standard DIN 53778: 20.000 d.p

98% hiding power when dry, at a yield of 8,79 m²/l, according to the ISO 6504-1. (Performance may vary depending on surface, dilution and colour).



TECHNICAL CHARACTERISTICS

Referencia Color	MAGNUM ECOLOGICO BLANCO
Finish	.
Specific weight	1,47 ± 0,05 kg/l
Viscosity	60 +/- 5 PO
Solids in volume	37 ± 1
Solids in weight	59 ± 1
VOC	Cat. a/BA 75/30 (2007/2010): 0,81 g/l
Aproximated performance by coat	13-15 m ² /L
Dry to touch	(20°C HR: 60%): 1h
Dry to repaint	(20°C HR: 60%): 3-4h

Fecha de Alta

29-07-2011

Versión

2C - 04/12/2025

Colours

White

BL, IN and TR bases

In tinting, for maintenance of the ecolabel certificate, use the MontomixSystem colorants and follow the instructions of Colormont.

SURFACE PREPAIRING

New surfaces

Cement and concrete mortars:

1. Wait until fully set (min. 30 days).
2. Clean any efflorescence with a jet washer.
3. Neutralize alkaline surfaces.
4. Sand polished surfaces to create a rougher surface.
5. Clean the surface to remove foreign products.
6. Set crumbly substrates with Emulsión Fijadora or Fijamont.
7. Fill in defects in the substrate (see family 6).

Plaster, plaster-covered brick:

1. Wait until it is completely dry (max. 20% humidity).
2. Clean the surface to remove foreign products.
3. Clean any efflorescence with a jet washer.
4. Regulate surface absorption with sealer, fixer, or a diluted coat of the same product.
5. Sand polished surfaces to create a rougher surface.
6. Set crumbly substrates with Emulsión Fijadora or Fijamont.
7. Fill in defects in the substrate (see family 6).

Plasterboard partition walls:

1. Carry out a general sanding of the joints and putty fixing areas.
2. Then, clean them to ensure the substrate is free of dust, grease and other contaminants.
3. For application on coloured boards that tend to generate stains, apply Montoplac Sellador Antimanchas.

Restoring and maintenance

1. Completely remove old paint that is in poor condition or that is poorly-adhered.
2. Glossy surfaces should be thinned out to ensure good adhesion.
3. On painted surfaces, check that the paint is solid and well-adhered. Its condition must be assessed, in order to avoid possible incompatibilities. Dust and dirt must also be eliminated before repainting.
4. Apply filler (Plasmont) to any defects on the surface.
5. Pre-treat mouldy walls using Monto Limpia Moho.

WAY OF USE

Application notes

- Remove the product until perfectly homogeneous.
- Apply on clean and dry surfaces, removing dirt with soapy water. In the case of extreme dirt, it is advisable to use degreasing agents or cleaning detergents.
- Apply in accordance with requirements marked in the attached application table.
- Do not apply the product at temperatures below 5°C nor on surfaces exposed to strong sunshine.
- Maintain good ventilation conditions during the drying time.
- Do not apply whilst the relative humidity is above 80%.
- For a perfect finish we recommend applying with a spray gun, but if you do use a roller it should be one designed for varnishing.
- Do not wash for the first 24 days.
- Clean tools with water immediately after use.
- For spraying with Airless equipment, use 15 to 23 inch nozzles, pressure 150 bar.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	5-20%
Roller	5-20%
Air-less gun	10-30%
Air-mix gun	10-30%

Fecha de Alta

29-07-2011

Versión

2C - 04/12/2025

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Inner painted old work in good state			
MAX			
STD	Magnum Ecológico Diluido		Magnum Ecológico
Inner painted old work in good state			
MAX	Eliminar + Fijador	Magnum Ecológico	Magnum Ecológico
STD	Eliminar + Magnum Ecológico Diluido		Magnum Ecológico
Project			
MAX	Fijador	Magnum Ecológico	Magnum Ecológico
STD	Magnum Ecológico Diluido		Magnum Ecológico
Drywall (gypsum plasterboard)			
MAX	Magnum Ecológico Diluido	Magnum Ecológico	Magnum Ecológico
STD	Magnum Ecológico Diluido		Magnum Ecológico

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

15 L
Canned bases 0.75 L, 4 L, 12 L