

CONVERPLUS ANTISILICONAS



FAMILY PRODUCTOS PARA USO ESPECIFICO
LINE ADITIVOS

DESCRIPTION AND NATURE

Silicone oil in solution form, to be added to MONTÓ manufactured pigmented and transparent solvent based paints. Specifically formulated to prevent the forming of cracking and other superficial faults or imperfections.

USAGES

Outdoors/Indoors

Designed to eliminate surface defects due to poor paint levelling, such as craters, fish-eyes or wrinkles, caused by a contaminating undercoat.

Designed to restore painted surfaces that have been contaminated with silicone oil or silicones

Designed to eliminate poor levelling caused by the evaporation of solvents.

Designed to eliminate "overspray" in paint gun applications.

In solvent-based paints

PROPERTIES

Reduce the surface tension

Reduce the inter-coats tension

Improves the tension balance between products with different polarity

Hides superficial defects as crates, fringes, orange skin appearance...

Hides defects caused by an unusual velocity dryness due to extreme solvent evaporation

Hides defects caused by high temperatures application which provokes an excessive solvent evaporation

TECHNICAL CHARACTERISTICS

Referencia Color	CONVERPLUS ANTISILICONAS
Mixture relation	1-2% en volumen respecto a la pintura a aditar
Finish	Base painting
Aproximated performance by coat	Depending of product usage

Colours	Colorless
---------	-----------

SURFACE PREPAIRING

New surfaces

As per product to which is to be added. This product should only be added at the top coat phase.

Restoring and maintenance

As per product to which is to be added. This product should only be added at the top coat phase.

WAY OF USE

Application notes

- This product should only be added those products indicated under recommended applications section.
- Paint or varnish to which this product is to be added should be perfectly homogenized.
- Follow recommended addition proportions indicated under application systems section.
- Mixture of varnish/paint + converplus antisilicona should be perfectly homogenized.
- Dilute the application viscosity with the solvent recommended for the product to be added.
- This product should only be added at the top coat process.

Solvent for dilution and cleaning

Solvent 1405

CONVERPLUS ANTISILICONAS

Way of use

Aproximate dilution

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
On usualy surfaces			
MAX			
STD	Idem que los productos a los que se adiciona	Idem que los productos a los que se adiciona	Producto de acabado

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 18 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS