

Fecha de Alta

13-08-2021

Versión

4 - 07/01/2026



FAMILY ESMALTES
LINE SPRAY MULTISOPORTE

DESCRIPTION AND NATURE

High-gloss spray to achieve a polished Gold or polished Chrome effect on the surface to be painted. Decorative finish, avoid scratching.

USAGES

Indoors
Glass
Plastic previously printed
Wood after priming
Metal after priming
On supports previously painted with primer
PVC and plastic (conduct a previous adhesion test)

PROPERTIES

Surface leveling
Fast drying
Easy application
Metallic glossy finishes highly decorative
Good adhesion
Glossy finish
High level of coverage.
With ageing, the gloss may decrease.
Smooth and fine finish
Do not wash aggressively.

TECHNICAL CHARACTERISTICS

Referencia Color	MONTOSPRAY CROMADO ORO
Aproximated performance by coat	Depending of product usage
Dry to touch	10min
Dry to repaint	60min
Colours	Gold, Chrome

SURFACE PREPAIRING

New surfaces

New woods:

- The surface must be free of foreign products and/or residues.
- Apply on wood with a moisture content lower than 12%.
- Apply on healthy wood, well degreased, dust-free and dry.
- Sand and remove possible glue residues on assemblies and machining faults.
- If the wood shows signs of ageing, it must be previously sanded and the dust removed by brushing or any other mechanical means.
- Protect the areas that we do not want to paint.
- Eliminate, in general, products that are poorly adhered or in poor condition.

Iron, derived metals and other metals:

- The surface must be free of foreign products and/or residues.
- The surface must be degreased, clean and dry.
- On rusty surfaces, we must eliminate the rust by the usual means recommended by Montó with any rust inhibitor manufactured by our Company, which should be applied in advance.

Fecha de Alta

13-08-2021

Versión

4 - 07/01/2026

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 48 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.4 L