

Fecha de Alta

14-09-2021

Versión

3 - 08/01/2026



FAMILY

ESMALTES

LINE

SPRAY MULTISOPORTE

DESCRIPTION AND NATURE

Marking paint for works, for fast and accurate marking and lettering on asphalt, concrete, masonry, pavers, wood, earth, stone, etc.

USAGES

Indoors/Outdoors

Wood

Construction

Ground

PROPERTIES

Fast drying

Easy to apply and repaint

Adhesion on wet surfaces

High level of coverage.

TECHNICAL CHARACTERISTICS

Referencia Color	MONTOSPRAY MARCAJE AMARILLO
Aproximated performance by coat	Depending of product usage
Dry to touch	30min
Dry to repaint	24h
Colours	Yellow 201, Red 202

SURFACE PREPAIRING

New surfaces

Restoring and maintenance

WAY OF USE

Application notes

- Shake the container for approximately 3 mins.
- Does not need cleaning due to its exclusive self-cleaning system.
- Apply at a distance of between 5 and 15cm.
- The 500ml container can mark up to a total of 220m.

Solvent for dilution and cleaning

Solvent 1406-05

Way of use

Approximate dilution

Fecha de Alta

14-09-2021

Versión

3 - 08/01/2026

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Asphalt			
MAX	Montospray Marcaje		Montospray Marcaje
STD			Montospray Marcaje
Wood			
MAX	Montospray Marcaje		Montospray Marcaje
STD			Montospray Marcaje
Works			
MAX	Montospray Marcaje		Montospray Marcaje
STD			Montospray Marcaje

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 48 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.5 L