

Fecha de Alta

13-08-2021

Versión

4 - 08/01/2026



FAMILY

ESMALTES

LINE

SPRAY MULTISOPORTE

DESCRIPTION AND NATURE

Container loaded with propellant, solvents and additives to be filled with solvent paints. Compatible with most paints, guaranteeing correct application. Ideal for repairing specific points or repainting specific areas.

The loaded product is not modified, so its properties align with those defined in its Technical Data Sheet.

Tested with Montosisntétic, Marisma, Fast Drying Enamel, Luxatin, Ferrorite, Synthetic Varnishes, Montoxyl Classic, Teak Oil...for other products please consult.

USAGES

PROPERTIES

TECHNICAL CHARACTERISTICS

Referencia Color	MONTOSPRAY PREFILL
Aproximated performance by coat	Depending of product usage

SURFACE PREPARING

New surfaces

Follow the indications of the filled product.

Restoring and maintenance

Follow the indications of the filled product.

WAY OF USE

Application notes

- Shake the container vigorously for about 2 minutes to homogenise its contents perfectly.
- Carry out application tests in a non-visible place.
- Protect areas that are not to be painted.
- Apply at a distance of 25-30cm from the surface in light, criss-cross strokes.
- Do not apply the product at high temperatures, or on surfaces exposed to strong sunlight.
- Maintain good ventilation conditions during the drying time.
- Do not apply while the relative humidity is above 80%.
- Do not use at temperatures below 15°C.
- When finished, empty the contents of the cannula by dosing with the container upside down.

Solvent for dilution and cleaning

Solvent 1406-05

Way of use

Aproximate dilution

Fecha de Alta

13-08-2021

Versión

4 - 08/01/2026

SYSTEM**Procedures depending of surface type****Primer****Intermedium****Finish****SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 48 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.4 L