



**FAMILY** ESMALTES  
**LINE** SPRAY MULTISOPORTE

## DESCRIPTION AND NATURE

Adhesive transparent primer for painting plastic surfaces. For painting plastic parts of cars, garden furniture and hard plastics in general.

## USAGES

Indoors/Outdoors

Plastic

Hard plastics: Polyurethane (PUR), Polystyrene (PS), Polyamide (PA), Modified Polypropylene (EPDM), ABS, Fibreglass, PVC

## PROPERTIES

Adherence  
Fast drying  
Easy application

## TECHNICAL CHARACTERISTICS

Referencia Color MONTOSPRAY PRIMER PLASTICOS TRANSPARENTE

Aproximated performance by coat Depending of product usage

Dry to touch 15min

Dry to repaint 30min

## SURFACE PREPAIRING

### New surfaces

- The surface must be free of foreign products and/or residues.
- The surface must be degreased, clean and dry.
- We must protect the areas that we do not want to paint.

### Restoring and maintenance

1. On paints in good condition, sand to open the pore, checking that the adherence is perfect.
2. On paints in bad condition, remove it by mechanical or chemical means and proceed as if it were a new surface.

## WAY OF USE

### Application notes

- Shake the container vigorously for about 2 minutes to homogenise its contents perfectly.
- Carry out application tests in a non-visible place.
- Protect areas that are not to be painted.
- Apply at a distance of 25-30cm from the surface in light, criss-cross strokes.
- Do not apply the product at high temperatures, or on surfaces exposed to strong sunlight.
- Maintain good ventilation conditions during the drying time.
- Do not apply while the relative humidity is above 80%.
- Do not use at temperatures below 15°C.
- When finished, empty the contents of the cannula by dosing with the container upside down.
- Approximate yield per 400ml container 5-6 m<sup>2</sup> (two cross-coats). Do not give more than 2 cross layers.

### Solvent for dilution and cleaning

Solvent 1406-05

# MONTOSPRAY PRIMER PLASTICOS

## Way of use

## Aproximate dilution

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>Plastic</b>			
<b>MAX</b>	Montospray Primer Plásticos		Gama Montospray
<b>STD</b>	Montospray Primer Plásticos		Gama Montospray

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

Maximum recommended storage time : 48 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

0.4 L