

Fecha de Alta

13-08-2021

Versión

3 - 07/01/2026



**FAMILY** ESMALTES  
**LINE** SPRAY MULTISOPORTE

### DESCRIPTION AND NATURE

Special acrylic-based anti-stain spray paint. Suitable for sealing most stains such as nicotine, oil, moisture stains, tomato sauce, wine, tea, coffee...

### USAGES

Indoors/Outdoors  
Gypsum Board  
Cement  
Plaster  
Dripping effect  
Construction  
Plaster

### PROPERTIES

Anti-spots  
Smooth finish  
Fast action  
Good hiding power capacity

### TECHNICAL CHARACTERISTICS

|                                 |                               |
|---------------------------------|-------------------------------|
| Referencia Color                | MONTOSPRAY ANTIMANCHAS BLANCO |
| Aproximated performance by coat | Depending of product usage    |
| Dry to touch                    | 15min                         |
| Dry to repaint                  | 1h                            |

### SURFACE PREPARING

#### New surfaces

The surface must be clean and free of dust, oils and non-adherent materials. Use suitable solvents for cleaning. If the surface is very absorbent, more coats of the product will be necessary. Do not apply on fresh stains.

#### Restoring and maintenance

How to remove stains:

This will depend on the absorption level of the surface. Do not apply on fresh stains.

On nicotine, tea, coffee and water-based marker stains: apply minimum 2 cross-coats, allowing 10 minutes drying time between each one. Leave to dry for 24hrs and repeat if necessary.

On oil stains, tomato sauce, wine, vinegar, pencils and solvent-based markers: apply minimum 2 cross-coats, allowing 10 minutes drying time between each one. Leave to dry for 24hrs and repeat if necessary.

On lipstick stains: Wash the stained area with a damp cloth. Allow to dry and then apply minimum 2 cross-coats, allowing 10 minutes drying time between each coat. Leave to dry for 24hrs and repeat if necessary.

On soot stains: Wash the stained area with a damp cloth. Allow to dry and then apply minimum 2 cross-coats, allowing 10 minutes drying time between each coat. Leave to dry for 24hrs and repeat if necessary.

### WAY OF USE

#### Application notes

- Use the spray at 20-25°C. In cold temperatures, heat in a bain-marie, never in direct contact with flame.
- Shake the spray for 1 to 2 minutes to ensure good homogenisation.
- To ensure proper application, it is recommended to shake the product during use.

