

# MONTOSPRAY ANTICALORICO



**FAMILY** ESMALTES  
**LINE** SPRAY MULTISOPORTE

## DESCRIPTION AND NATURE

Spray enamel designed to withstand temperatures up to 600°C

## USAGES

Cement  
Plaster  
Brick  
Stone  
Iron  
Steel

## PROPERTIES

Adherence  
Resistance to the chemical attacks  
Fast drying  
Good coverage  
Strong resistance to the atmospherical factors  
Odourless when dry

## TECHNICAL CHARACTERISTICS

Referencia Color	MONTOSPRAY ANTICALORICO NEGRO
Aproximated performance by coat	Depending of product usage

Dry to touch	15min
Dry to repaint	24h
Colours	Black 904 and Silver 906

## SURFACE PREPARING

### New surfaces

Iron, derived metals and other metals:

- The surface must be free of foreign products and/or residues.
- The surface must be degreased, clean and dry.
- On rusty surfaces, we must eliminate the rust by the usual means recommended by Montó with any rust inhibitor manufactured by our Company, which should be applied in advance.
- We must protect the areas that we do not want to paint.
- Eliminate, in general, products that are poorly adhered or in poor condition.

Works (plaster, cement and derivatives, cardboard):

- Eliminate foreign products and/or residues.
- The surface must be degreased, clean and dry.
- Eliminate possible efflorescence using traditional methods.
- Eliminate, in general, products that are poorly adhered or in poor condition.

### Restoring and maintenance

Clean and proceed as with new surfaces.

