

MONTOXYL LASURE ACQUA ACABADO PIGMENTADO



FAMILY MADERA / SISTEMAS TINTOMÉTRICOS

LINE PROTECTORES (AGUA)

DESCRIPTION AND NATURE

Water-based pigmented wood stain. This open-pore treatment is easy to maintain and creates a breathable, elastic, protective film with excellent weather resistance. It can be tinted using a color mixing system.

USAGES

Exterior, on wood subject to risk class 3. Outdoors, without direct contact with soil or constant moisture.

Exterior/Interior.

In new and used woods.

For structures and beams, carpentry, vertical surfaces, garden furniture, etc.

Not recommended for carpet and decks.

PROPERTIES

- Non Yellowing
- No cracking at all
- Filling capacity
- Water steam transpirable
- Odourless when dry
- Withstands strong climate changes
- Flexible
- Microporous
- Highlights the wood's natural grain
- U.V. resistant
- Good applicability
- With IPBC as dry film protector
- Does not form blisters

TECHNICAL CHARACTERISTICS

Referencia Color	MONTOXYL LASURE ACQ.ACAB.PIGMENT.BLANCO
Finish	Semi-matt
Specific weight	1,24± 0,05 kg/l
Viscosity	40 +/- 5 PO
Solids in volume	34± 1
Solids in weight	48± 1
VOC	Cat. e/BA 150/130 (2007/2010):130,00 g/l
Aproximated performance by coat	8-12 m ² /L

Dry to touch	(20°C HR:60%):2-4h
Dry to repaint	(20°C HR:60%):12-24h
Colours	SSTT:

Classification	TR base (20) BL base (103) AFNOR NFT 36005 Familia I clase 7b2.
----------------	--

SURFACE PREPAIRING

New surfaces

New Wood:

MONTOXYL LASURE ACQUA ACABADO PIGMENTADO

1. The surface must be free of foreign matter and/or residue.
2. Apply to wood with a moisture content of less than 20%.
3. Apply to sound, well-degreased, dust-free, and dry wood.
4. For wood with internal resin stains (usually softwoods) and/or oily tropical woods, it will be necessary to clean them first with solvent.
5. Sand and remove any glue residue from joints and machining imperfections.
6. If the wood shows signs of aging, it must be sanded beforehand, removing dust by brushing or any other mechanical means.

Restoring and maintenance

Varnished or painted wood:

1. If varnished or lacquered with solvent-based products, these must be removed using a universal paint stripper or mechanical means, until bare wood is exposed.
2. If varnished with water-based products or stains, it can be sanded without complete removal and re-varnished.
3. In any case, check the adhesion of the new varnish over the existing one, and if in doubt, remove it completely.

WAY OF USE

Application notes

- Stir the product until completely homogenized.
- Apply to clean, dry surfaces.
- Sand beforehand to ensure good penetration and even coverage of the wood.
- Applying Montoxyl Lasur Fondo, after sanding, provides the best finishes and optimal coverage.
- Apply following the dilutions recommended in the Application Systems section.
- Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.
- Maintain good ventilation during the drying time.
- Do not apply in relative humidity above 80%.
- Avoid accumulation on the wood surface in all cases.
- For furniture and vertical surfaces.
- It can be applied without sanding between coats, although light sanding is recommended to ensure perfect adhesion, especially for woods prone to take out slivers.

Solvent for dilution and cleaning

Water

Way of use

Painting brush

Roller

Spray gun

Aproximate dilution

0-15%

0-15%

10-25%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Old/New interior Wood			
MAX	Decapar y/o Fondo lasure acqua o Montoxyl fondo	Montoxyl Lasure Acqua Pigmentado	Montoxyl Lasure Acqua Pigmentado
STD	Decapary/o Fondo lasure acqua o Montoxyl fondo		Montoxyl Lasure Acqua Pírgmentado
New wood/old outdoor			
MAX	Decapar y/o Anticarcoma Klearxyl Aqua 3	Fondo lasure acqua o Montoxyl fondo	Montoxyl Lasure Acqua Pigmentado
STD	Decapar y/o Fondo lasure acqua o Montoxyl fondo		Montoxyl Lasure Acqua Pírgmentado
varnished or painted wood			
MAX	Decapar+ Fondo lasure acqua o Montoxyl fondo	Montoxyl Lasure Acqua Pigmentado	Montoxyl Lasure Acqua Pigmentado
STD	Decapar+ Fondo lasure acqua o Montoxyl fondo		Montoxyl Lasure Acqua Pigmentado

501341

Fecha de Alta

29-03-2007

Versión

8 - 10/11/2025 :

MONTOXYL LASURE ACQUA ACABADO PIGMENTADO



SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L, 4 L